

Generating Rates		Prime	Standby
Power	kVA	1000	1100
Power	kW	800	880
Current	(cos Phi=0,8) A	1443	1588
Standard Voltage	V	400/231	400/231
Revolution Per Minute	r.p.m	1500	1500
Rated At Power Factor	Cos Phi	0,8	0,8

### Standard Features

- ✓ 4 stroke 1500RPM, water cooled heavy duty diesel engine
- ✓ Dry type replacable air filter
- ✓ Heat-resistant radiator for 50 °C
- ✓ Flexible oil pipes and oil draining valve
- ✓ Pre-heater
- ✓ 4 poles synchronotype, single bearing, brushless alternator
- ✓ Batteries and cables
- ✓ Electrostatic paint coated, steel, welded chassis
- ✓ Fuel tank housed in the chassis
- ✓ Industrial type silencer
- ✓ Electronic battery charger
- ✓ Electrical wiring diagram
- ✓ User manual and operating manual
- ✓ Protection system on manual run
- ✓ Lubrication oil and anti – freeze
- ✓ Electronic governor

### Optional Equipments

- ✓ Soundproof canopy
- ✓ Automatic transfer switch
- ✓ Circuit Breaker
- ✓ Trailer
- ✓ External fuel tank
- ✓ Heating system for fuel tank
- ✓ Oil heater
- ✓ Fuel filling system (Automatic / Manual)
- ✓ Analog indicators
- ✓ 1 Phase - 3 phase switch plugs
- ✓ Alarm system for fuel level
- ✓ Remote control and monitoring

**Prime Power :** Supplying of electrical power at variable load for an unlimited number of hours in the event of normal utility powerfailure according to ISO8528-1. 10% over load capability is available.

**Stand By Power :** Supplying of electrical power at variable load, in the event of normal utility power failure according to ISO8528-1. This rating is maximum power, no overload capability is available.

### Engine Specifications

Brand		SDEC
Model		6WTAA35-G31
Engine Power	(kWm / hp)	970 / 1320
Revolution Per Min	(r.p.m)	1500
Total Displacement	(L)	35,1
Cylinders Orientation		6 Vertical In-line
Broke x Stroke	(mm x mm)	186 x 215
Compression Orientation		15 : 1
Governor Type		Electronic
Aspiration System		Turbo AAC
Injection		Direct
Cooling		Water Cooled
Electrical System	(VDC)	24
Lub-oil Capacity	(L)	100
Engine Coolant Capacity	(L)	158
Fuel Tank Capacity	(L)	1400
Maximum Exhaust Temperature	(°C)	650
Maximum Exhaust Gas Flow	(m3/h)	162,6
Maximum Allowed Back Pressure	(kPa)	6
Cooling Air Flow	(m3/min)	-
Fuel Consumption 50 %	(L/h)	92,9
Fuel Consumption 75 %	(L/h)	136,6
Fuel Consumption 100 %	(L/h)	188,1

- ✓ Replacable cylinder jacket
- ✓ Dry type replacable air filter
- ✓ Heat-resistant radiator for 50 °C

### Alternator Specifications

Standard Voltage	(V)	400/231
Frequency	(Hz)	50
Stationary Voltage Regulation	(±)	1
Short Circuit Current		300
Insulation		H
Protection		IP 23
Efficiency	(%)	95,1
Overloading		1 Hour - %110
Rated At Power Factor	(cos Phi)	0,8
Total Harmonic Distortion Rate		2
Connection Style		Star
Number of Pole		4
Number of Bearing		Single

- ✓ Self-cooled
- ✓ Electronic type automatic voltage regulator (AVR)
- ✓ 4 poles, self-excitation, brushless, synchrontype alternator

### Dimensions Without Canopy and Weight

WIDTH x LENGTH x HEIGHT	mm	2200x5500x2550
Wet Weight	kg	8578

### Dimensions With Canopy and Weight

WIDTH x LENGTH x HEIGHT	mm	2200x6000x2750
Wet Weight	kg	10288



### Control Panel Features

- ✔ Diesel and gas genset support
- ✔ 400Hz operation support
- ✔ 400 event logs full snapshot
- ✔ Multiple Automatic test program
- ✔ 3 level configuration password
- ✔ 128x64 graphical LCD display
- ✔ Downloadable language
- ✔ Waveform display of V&I
- ✔ Harmonic analysis of V&I
- ✔ Synchroscope & check synch
- ✔ 16 Amp MCB & GCB outputs
- ✔ 8 configurable digital outputs
- ✔ Outputs expandable to 40
- ✔ 4 configurable analog outputs
- ✔ Battery charge run enabled
- ✔ Weekly Operation Schedule
- ✔ Dual mutual standby with equal aging of gensets
- ✔ Manual speed fine adjust some ECU's
- ✔ Automatic fuel pumpcontrol
- ✔ Disable protection feature
- ✔ Excess protection power
- ✔ Reverse power protection
- ✔ Overload IDMT protection
- ✔ Load shedding, dummy load
- ✔ Multiple load management
- ✔ Waveform display of V&I
- ✔ Battery back-up real time clock
- ✔ Idle speed control
- ✔ All parameters front panel editable
- ✔ Multiple nominal conditions
- ✔ Contactor & MCB drive
- ✔ 4 quadrant genset power counters
- ✔ Mains power counters
- ✔ Fuel filling counter
- ✔ Fuel consumption counter
- ✔ Free configuration software
- ✔ Allow SMS controls
- ✔ Mobile genset support
- ✔ Automatic GSM geo-location
- ✔ GPS connectivity (USB & RS232)
- ✔ Modem & ethernet diagnostic
- ✔ Configurable through USB, RS-485, Ethernet and GPRS
- ✔ Ready for central monitoring Ethernet and GPRS