

Generating Rates		Prime	Standby
Power	kVA	656	722
Power	kW	525	578
Current	(cos Phi=0,8) A	949	1043
Standard Voltage	V	400/230	400/230
Revolution Per Minute	r.p.m	1500	1500
Rated At Power Factor	Cos Phi	0,8	0,8

### Standard Features

- ✓ 4 stroke 1500RPM, water cooled heavy duty diesel engine
- ✓ Dry type replacable air filter
- ✓ Heat-resistant radiator for 50 °C
- ✓ Flexible oil pipes and oil draining valve
- ✓ Pre-heater
- ✓ 4 poles synchronotype, single bearing, brushless alternator
- ✓ Batteries and cables
- ✓ Electrostatic paint coated, steel, welded chassis
- ✓ Fuel tank housed in the chassis
- ✓ Industrial type silencer
- ✓ Electronic battery charger
- ✓ Electrical wiring diagram
- ✓ User manual and operating manual
- ✓ Protection system on manual run
- ✓ Lubrication oil and anti – freze

### Optional Equipments

- ✓ Soundproof canopy
- ✓ Automatic transfer switch
- ✓ Circuit Breaker
- ✓ Trailer
- ✓ External fuel tank
- ✓ Electronic governor
- ✓ Heating system for fuel tank
- ✓ Oil heater
- ✓ Fuel filling system (Automatic / Manual)
- ✓ Analog indicators
- ✓ 1 Phase - 3 phase switch plugs
- ✓ Alarm system for fuel level
- ✓ Remote control and monitoring

**Stand By Power :** Supplying of electrical power at variable load, in the event of normal utility power failure according to ISO8528-1. This rating is maximum power, no overload capability is available.

**Prime Power :** Supplying of electrical power at variable load for an unlimited number of hours in the event of normal utility powerfailure according to ISO8528-1. 10% over load capability is available.

### Engine Specifications

Brand		SDEC
Model		SC27G830D2
Engine Power	(kWm / hp)	610
Revolution Per Min	(r.p.m)	1500
Total Displacement	(L)	26,6
+Cylinders Orientation+		12 V TİPİ
Broke x Stroke	(mm x mm)	135 x 155
Compression Orientation		16 ; 01
Governor Type		ELEKTRONİK
Aspiration System		TURBO AAC
Injection		DİREKT
Cooling		SU SOĞUTMALI
Electrical System	(VDC)	24
Lub-oil Capacity	(L)	65
Engine Coolant Capacity	(L);	48
Fuel Tank Capacity	(L)	1160
Maximum Exhaust Temperature	(°C)	600
Maximum Exhaust Gas Flow	(m3/h)	99,5
Maximum Allowed Back Pressure	(kPa)	6
Cooling Air Flow	(m3/min)	39
Fuel Consumption 50 %	(L/h)	74,1
Fuel Consumption 75 %	(L/h)	106,7
Fuel Consumption 100 %	(L/h)	141,0

- ✓ Replacable cylinder jacket
- ✓ Dry type replacable air filter
- ✓ Heat-resistant radiator for 50 °C

### Alternator Specifications

Standard Voltage	(V)	400/230
Frequency	(Hz)	50
Stationary Voltage Regulation	(±)	1
Short Circuit Current		300
Insulation		H
Protection		IP 23
Efficiency	(%)	95
Overloading		1 SAAT - %110
Rated At Power Factor	(cos Phi)	0,8
Total Harmonic Distortion Rate		2
Connection Style		YILDIZ / STAR
Number of Pole		4
Number of Bearing		TEK / SINGLE

- ✓ Self-cooled
- ✓ Electronic type automatic voltage regulator (AVR)
- ✓ 4 poles, self-excitation, brushless, synchrontype alternator

### Dimensions Without Canopy and Weight

LENGTH x HEIGHT x WIDTH	mm	3900x1900x2350
Wet Weight	kg	4751



### Dimensions With Canopy and Weight

LENGTH x HEIGHT x WIDTH	mm	4800X1900X2710
Wet Weight	kg	5926



### Control Panel Features

- ✓ Diesel and gas genset support
- ✓ 400Hz jeneratör desteği
- ✓ 400xölcüm değerli olay kaydı
- ✓ Çoklu otomatik test programı
- ✓ 3 seviyeli program şifresi
- ✓ 128x64 piksel grafik LCD
- ✓ Dil yükleme
- ✓ Akım-gerilim dalga şekli
- ✓ Akım-gerilim harmonik analiz
- ✓ Senkroskop ve senkron rölesi
- ✓ 16 Amp / 250V ŞK /JK çıkışları
- ✓ 8 adet programlı dijital giriş
- ✓ Çıkışlar 40 adede artırılabilir
- ✓ 4 adet programlı analog giriş
- ✓ Battery charge run enabled
- ✓ Weekly Operation Schedule
- ✓ Dual mutual standby with equal aging of gensets
- ✓ Manual speed fine adjust some ECU's
- ✓ Automatic fuel pumpcontrol
- ✓ Disable protection feature
- ✓ Excess protection power
- ✓ Reverse power protection
- ✓ Overload IDMT protection
- ✓ Load shedding, dummy load
- ✓ Çoklu yük atma programları
- ✓ Waveform display of V&I
- ✓ Battery back-up real time clock
- ✓ Idle speed control
- ✓ All parameters front panel editable
- ✓ Multiple nominal conditions
- ✓ Contactor & MCB drive
- ✓ 4 quadrant genset power counters
- ✓ Mains power counters
- ✓ Fuel filling counter
- ✓ Fuel consumption counter
- ✓ Free configuration software
- ✓ Allow SMS controls
- ✓ Mobile genset support
- ✓ Otomatik GSM konum belirleme
- ✓ GPS connectivity (USB & RS232)
- ✓ Modem & ethernet diagnostic
- ✓ Configurable through USB, RS-485, Ethernet and GPRS
- ✓ Ready for central monitoring Ethernet and GPRS